

Model G-LD Telem manipulator

The G-LD telem manipulator is a one-piece telem manipulator designed for use in small working areas.

Utilizing the smaller, light-duty capacity of the Model G, the Model G-LD was developed as a very compact telem manipulator that could be utilized in small gloveboxes. The Model G-LD does not have electrically-indexed motions. Instead, it can be customized with Manual Y Indexing and Motion Locks. The result is a compact, lightweight, inexpensive, customizable telem manipulator that works well within the confines of a small enclosure.

- Light-Duty
- Compact size for small working areas
- Multiple options available for customization



Application Solutions:



POTENT



ASEPTIC/POTENT



RADIOPHARMA

LIFE SCIENCE

NUCLEAR

RH_GLD_0118_US

Model G-LD Telemanipulator

EXTENDED LENGTH

5 ft [1.52 m]

CAPACITY

10 lb [4.5 kg]



MOUNT OPENING DIAMETER

7.5 in [190.5 mm] or Custom Upon Request

MOUNTING HEIGHT

84 in [2.13 m] or Custom Upon Request

ONE-PIECE SYSTEM

UNSEALED THRU-TUBE

CUSTOMIZABLE

Compact & Lightweight Design for Small Enclosures

Features Available

- NEW** VERSA® VR8 Opposed Grip Handle with improved ergonomics for operator comfort
- NEW** Small 3-piece Tong for light duty applications where a sealed tong is required
- Manual Y Indexing

Configuration Options

Shielding

Tongs/Jaws

Handle

Indexing

Motion Locks

Booting

Available Accessories

- Tamper Locks
- Load Hook
- Change Fixture
- Installation/Removal Cart
- Storage Cart
- Wall Tube



VERSA® VR8
Opposed Grip Handle



Small 3-piece
Tong



Boot/3-piece Tong

RH_GLD_0118_US